



Piston Compressors

Single Phase CPBA | CPDA | CPRB



People.
Passion.
Performance.



People. Passion. Performance.



CPRB-6



CPRB-50 FIBRE



CPDA-2524



CPDA-2550

The perfect solution for your home and professional workshop

Easy to use, efficient and lightweight, we have a wide variety of Chicago Pneumatic single phase air compressors. High flexibility and highly reliable, they provide the air solution you need when all you need is a solid source of compressed air.

CPRB oil-less units minimize risks of oil-spilling are suitable for fibre blowing tasks. This range that have compact configurations and vessel sizes provide top flexibility to match the demand of any customer.

CPDA direct driven oil-lubricated compressors are suitable for your DIY and workbench applications.

Technical Table	Displacement		Maximum Pressure	Motor power		Noise level	Tank	Dimensions	Weight
	l/min	cfm		bar	HP				
Oil-less									
CPRB-6	180	6.4	8	1.5	1	90	6	330 x 360 x 350	9.5
CPRB-50 FIBRE	200	7	10	2	1.5	90	50	780 x 450 x 710	36
Oil-lubricated Direct Driven									
CPDA-2524	269	9.5	10	2.5	1.8	95	24	700 x 350 x 325	24
CPDA-2550	269	9.5	10	2.5	1.8	95	50	790 x 330 x 590	37

Performance and reliability when it matters

These belt driven units with a one stage compression are easy and efficient to handle, lightweight with a continuous duty cycle.

CPBA-2550 is our 2.5HP version with a 10 amp plug for versatility. This belt driven range have legs that are widely positioned, working to prevent from tipping over and making them easy to transport; being the ultimate workshop partner.

CPBA-5530E twin tank petrol powered unit to deliver professional contractors the power they need. Suitable for all terrain, construction, farm jobs, fencing and work sites.



CPBA-3100



CPBA-5530E

Technical Table	Displacement		Maximum Pressure	Motor power		Noise level	Tank	Dimensions	Weight
Model	l/min	cfm	bar	HP	kW	dB(A)	L	L x W x H (mm)	Kg
Oil-lubricated Belt Driven									
CPBA-2550	246	8.7	10	2.5	1.8	93	50	840 x 440 x 735	58
CPBA-350	370	13	10	3	2.2	93	50	840 x 440 x 755	64
CPBA-3100	370	13	10	3	2.2	93	100	940 x 510 x 910	81
Oil-lubricated Petrol Driven									
CPBA-5530E	351	12.4	10	5.5	4.1	99	15 (twin)	1168 x 584 x 660	100



Efficiency

Highly efficient motors with copper windings to protect from oil, water and dust.



Quality

Reliable operation with high-quality Condor pressure switch installed for the models.



Stability

Wheels and legs are positioned widespread to maximise stability of the units.



Easy maintenance

All the main components are easily accessible, ensuring fast and simple maintenance.

People. Passion. Performance.



Innovative Hose Reel Piston

One-of-a-Kind Design

Branded shroud with appealing, slim design. Lightweight and easy to install everywhere.

Plug-and-Play

It runs continuously and features a user-friendly start-stop button and a max valve which is set at 8 bar.

Extremely Compact Size

Fully-enclosed pump and 10-meter hose reel.

Technical Table	Displacement		Maximum Pressure	Motor power		Noise level	Speed	Dimensions	Weight
Model	l/min	cfm	bar	HP	kW	dB(A)	rpm	L x W x H (mm)	Kg
Oil-less Hose Reel Piston									
1129740432	160	5.6	8	1.5	1	68	2450	400 x 310 x 410	8.5