

CPRD 8270 NS39 (B60)

1. CE certified vessel
2. Strong reliable power
3. Reliable pressure switch
4. Safe and robust protection
5. High performance pumps



CPRD 4200 NS29S (B49)



CPRD 6270 NS39 (B59)




CPRD 10270 NS59S (B70)

Professional top performance and reliability

Belt driven units are designed to deliver more air and higher pressures to increase the number of possible applications.


Strong components, optimal air flows, inter- and aftercoolers, guarantee the reliability and efficiency required in medium to bigger sized workshops and service stations.

Technical Data		Displacement		Motor power	Pressure	Receiver	Weight	Dimension
Model	Pump material	l/min	cfm	hp	bar	litre	kg	(LxWxH) mm
CPRD 4200	ALU	514	18.2	4	11	200	137	1500x450x960
CPRD 6270	ALU	653	23.1	5.5	11	270	180	1520x590x1260
CPRD 8270	ALU	827	29.2	7.5	11	270	210	1520x590x1260
CRPD 10270	ALU	1210	42.7	10	11	270	220	1520x590x1260




Top performance

Dual compression for higher pressures and higher air delivery.




Efficiency

Inter- and aftercoolers reduce the air temperature.




Strong and robust

Impressive and reliable top pump.



Stability

Two blockable front wheels.



User comfort

Silencing inlet filters for user friendly use.