



Chicago
Pneumatic



SIZE MATTERS

New Ultra Compact Tool

#CPsizeMatters



- ✓ 20% lighter than the previous generation
- ✓ Improved power:
460 ft.lbs / 625 Nm
of max. torque in reverse

CP7732C

1/2" Stubby Impact Wrench



**Vehicle
Service**Tools

People. Passion. Performance.

2.2 lbs. - 1.0 kg
20%
LIGHTER
Ultra Lightweight

CP7732C

1/2" Stubby Impact Wrench



4-1/4 IN. - 108 MM ONLY

POWERFUL

460 ft.lbs - 625 Nm of maximum torque in reverse

HIGH DURABILITY & ROBUST

- Jumbo hammer mechanism
- Steel motor
- Aluminum clutch housing

COMFORT & LIGHTWEIGHT

- Composite housing
- Curved handle with Thermo-Plastic Rubber injected housing, for a durable and comfortable grip

CONVENIENT


Socket retainer ring

EASY OPERATION

- S2S "Side-to-side": 1 handed Forward - Reverse operation
- New power setting system: 1 handed-operation behind the trigger
 - 2 positions in reverse: maximum and low torque
 - 2 positions in forward: maximum and low torque

GREAT CONTROL

Full teasing trigger



DIMENSIONS

A		B		C	
in.	mm	in.	mm	in.	mm
4.3	108	7.5	190	2.6	65

Model	Part number	Anvil	Speed	Working torque		Max torque		Weight		Length		Air cons. average		Air cons. @ load		Sound level	Vibration	Inner hose diameter		Air inlet
		inch	RPM	ft-lbs.	Nm	ft-lbs.	Nm	lbs	kg	inch	mm	cfm	l/s	cfm	l/s	dBA	m/s ² (k)	in	mm	in
CP7732C	894 107 7321	1/2	9,410	52 - 285	70 - 387	460	625	2.2	1.0	4 1/4	108	5.5	2.6	22	10.2	95.5	10.8 (1.42)	3/8	10	1/4

All models: Hose int. 3/8" (10 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check tool documentation.

STANDARD OR MAGNETIC 1/2" SOCKET SETS

Model	Part #	Type	Pc	Set content
SS4114	894 016 4458	Metric	14	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26 & 27 mm
SS4013	894 016 4465	SAE	13	7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, & 1-1/4"
SS4112G	894 016 4462	Metric	12	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 & 21 mm
SS4011G	894 016 4469	SAE	11	3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16 & 1"

2 STAGE COMPOSITE 1/4" FRL

Part #	Type	Max. Flow Rate	
		cfm	l/sec
894 017 1944	NPT	74	34
894 017 1927	BSP	74	34

TUNE-UP KIT

Model	Tune-up Kit
CP7732C	894 017 3823

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check www.cp.com website for more information.



AshAir

Compressed Air & Vacuum



0800 274 247 www.ashair.co.nz

www.cp.com