Chicago Pneumatic



Vehicle Service

People. Passion. Performance.





High Performance 1/2" Impact Wrench

EXTREME TORQUE

- 955 ft.lbs 1300 Nm max in reverse
- Twin Hammer Mechanism

COMPACT AND LIGHTWEIGHT

- 6.7 in 171 mm length
- 3.95 lbs. 1.8 kg



DIMENSIONS

MODEL	ļ	4	E	3	С			
	in.	mm	in.	mm	in.	mm		
CP7749	6.7	171	7.67	195	4.84	123		
CP7749-2	8.7	221	7.67	195	4.84	123		





- Side-2-Side Forward/ Reverse switch
- Easy to use with one hand

GREAT CONTROL

- 2 stage trigger
- Bi-material for a better grip

EASY OPERATION

NEW power setting system positionned behind the trigger

- 1 hand-operation
- Accessible for left or right handed operators

INSULATION & COMFORT

- Curved handle with Thermo-Plastic Rubber injected in housing for a durable and comfortable grip
- Resistant to most chemicals used in workshops

Model	Part number	Anvil	Square Drive	Speed	Wor Tor	king que	Max T	orque	We	ight	Consu	ir mption rage			Sound Level	Vibration
		inch	inch	RPM	ft-lbs.	Nm	ft-lbs.	Nm	lbs	kg	cfm	l/s	cfm	l/s	dBA	m/s² (k)
CP7749	894 107 7491	Short	1/2	7000	100 - 522	135 - 704	955	1300	3.95	1.8	6.2	3	25	12	95	10.9 - (2.7)
CP7749-2	894 107 7493	2"	1/2	7000	100 - 522	135 - 704	955	1300	4.6	2.00	6.2	3	25	12	95	10.9 - (2.7)

Listed specifications are for reference only. Please check tool documentation.



SOCKETS

Scan the QR code to access our sockets catalog

All sockets sizes and types available on **www.cp.com**



PROTECTIVE COVER

Description Part number
Tool boot 894 017 3269
Available in March 2015

TUNE-UP KIT

Model Tune-up Kit

CP7749 & 894 017 2707

CP7749-2

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check www.cp.com website for more information.





0800 274 247 www.ashair.co.nz www.cp.com