


Benefits

- ▶ Ideal for General Maintenance applications
- ▶ Powerful motor and durable clutch
- ▶ Operator comfort


Features

- ▶ 3/4" impact wrench with Ring retainer
- ▶ Twin hammer clutch
- ▶ High power: 1,200 ft.lbs (1,627 Nm)
- ▶ Combined power regulator with forward/reverse

Technical description		
Part number	8941077630	
Model	CP7763	
Handle type	Pistol	
Square drive	3/4"	
Working Torque Range (fwd)	136-1288 Nm	100-950
Maximum Torque (reverse)	1630 Nm	1200 ft.lbs
Free speed	6300 rpm	
Blows per minute	900	
Net weight	5.25 kg	11.57 lb
Power/weight ratio	310.5 Nm/kg	103.7 ft.lb/lb
Length	229 mm	8.8"
Side to center	45 mm	1.8"
Average air consumption	3.5 l/s	7.5 cfm
Actual air consumption	14.2 l/s	30 cfm
Air inlet thread size	0.375 "	
Min. hose size	13 mm	1/2"
Sound pressure	96 db(A)	
Sound Power	107 db(A)	
Vibration (ISO-8662-7)	9 m/s ²	
Vibration α (ISO-28927-2)	10.4 m/s ²	
Vibration K (ISO-28927-2)	4.2 m/s ²	
Socket retainer	Friction ring	
Clutch type	Twin hammer	

