

PRODUCT INFORMATION



AIRnet is a reusable aluminum piping system designed in line with EN 13480-3 to deliver a fast, easy, and reliable distribution network for Compressed Air, Nitrogen, and Vacuum.



PIPES 20 - 25 - 40 - 50 - 63 - 80 - 100 - 158 mm

Applications	Compressed Air, Nitrogen, and Vacuum	EN standard
Material	Extruded aluminum alloy EN AW-6060 T6	EN 755-2
Safety factor	4 for all diameters	
Working pressure	Max 16 bar(g) for 20 - 25 - 40 - 50 - 100 - 158 mm Max 13 bar(g) for 63 - 80 mm	
Working temperature	-20°C to 80°C for 20 - 25 - 40 - 50 - 100 - 158 mm -20°C to 70°C for 63 - 80 mm	
Vacuum level	13 mbar(a)	
Dewpoint	Lowest allowable pressure dewpoint is -70°C	
Outside treatment	Polyester powder paint (QUALICOAT certified)	
Inside treatment	Chrome free conversion treatment	
Colors	Blue RAL 5012 and Green RAL 6018 (only 20 - 25 mm)	



FITTINGS 20 - 25 - 40 - 50 mm (PF series)

Connection	Push to fit technology	EN standard
Materials	Engineered polymer PA6 - GF30 fiberglass reinforcement Aluminum high pressure die casting EN AC-46100 Wrought aluminum alloy EN AW-6082	EN 1706 EN 755-2
Seal fittings	NBR 70 Sh A (PTFE coating on pipe seal)	



FITTINGS 63 - 80 mm

Connection	Torque to grip technology	EN standard
Materials	Aluminum high pressure die casting EN AC-46100 Aluminum permanent mold casting EN AC-43100 Wrought aluminum alloy EN AW-6082	EN 1706 EN 1706 EN 755-2
Seal fittings	NBR 70 Sh A	



FITTINGS 100 mm

Connection	Bolt clamp technology	EN standard
Materials	Aluminum permanent mold casting EN AC-43100 High yield strength steel for cold forming EN 1.0976	EN 1706 EN 10149-2
Seal fittings	NBR 70 Sh A	



FITTINGS 158 mm

Connection	Bolt clamp technology	EN standard
Materials	Aluminum permanent mold casting EN AC-43100 Stainless Steel EN 1.4301	EN 1706 EN 10088-2
Seal fittings	NBR 70 Sh A	

PRODUCT INFORMATION



AIRnet technologies and innovations are based on technical expertise gained from more than 140 years of experience with pressurized air applications and equipment.


AIRNET IS FAST AND EASY TO INSTALL AND FLEXIBLE FOR THE FUTURE

TIME AND TOOLING

- Quick connections with no need to crimp, thread, solder or glue the pipe
- No heavy tooling or machinery required
- PF series can be connected to any existing network via simple use of adaptor unions and nipple sockets
- PF series is assembled by hand, a push of the pipe into the fitting is all it takes

MODULARITY

- Easy to handle and easy to work with lightweight materials
- Modular design supports extensions and modifications to meet new demands
- Components are interchangeable and reusable after disassembly
- Quickdrops are easily mounted, both horizontally and vertically



Quickdrop design safeguards leaktight and condensate free droplines



AIRNET IS RELIABLE, SAFE, AND MAINTENANCE FREE

SUSTAINABILITY

- Optimized inner body design minimizes flow resistance and pressure drop in the fittings
- Low friction factor and seamless connections minimize pressure drops in the pipe network
- Superior sealing technology ensures a leak free system and maintains performance over time
- Durable and corrosion resistant materials offers a maintenance free system

SAFETY

- Safety factor of 4 for all diameters
- Camera control and automatic assembly guarantee zero defect manufacturing
- Plastic components and pipe clips comply to UL 94 HB and UL 94 V-2 for flammability
- Torque indicators ensure sufficient torquing



White torque indicators (PF Series)

AshAir

Compressed Air & Vacuum



www.ashair.co.nz

0800 274 247