



Blowers

Lobe Blowers for Dairy Industry



LTH-065 | LTH-080 | LT-100

Roots Blowers For Dairy applications

Technical Data

LTH-065

Nominal Motor Power	Blowers Speed	Nominal Flow @ -50 kPa
kW	rpm	l/min
7.5	2000	1800
11	2500	2500
11	3000	3300
15	3500	4200
15	4000	5000

LTH-080

Nominal Motor Power	Blowers Speed	Nominal Flow @ -50 kPa
kW	rpm	l/min
11	1500	2000
15	2000	3500
15	2500	5200

LT-100

Nominal Motor Power	Blowers Speed	Nominal Flow @ 50 kPa
kW	rpm	l/min
11	1000	2000
11	1150	2500
11	1300	3200
11	1450	3800
15	1600	4500
15	1750	5000

Dimensions

Model	Dimensions, mm			Main body weight
	Length	Width	Height	kg
LTH-065	1189	565	1140	255
LTH-080	1461	1520	700	485
LT-100	970	785	615	230

About us

Ash Air started in 1979. Through organic and acquisition growth we soon became the largest company in New Zealand specialising in the compressed air and vacuum service and supply industry. Ash Air sells Chicago Pneumatic, Alup and Pneumatech brands directly from the factories in Belgium and Italy. Ash Air now comprises of 13 locations nationally with over 115 staff and hundreds of years of combined experience.

Efficient Blowers with Low Life Cycle Costs

The range of Longtech blowers is specifically designed for dairy application.

Performance, tailored to the typical New Zealand shed sizes, low noise level and long service life time provides you with a trouble-free and cost-effective solution to meet your needs.

These blowers are made to be an easy and cost-efficient upgrade from liquid ring pump system.



Low Noise operation

- Low running speed;
- Three lobe profile



Replacement of liquid ring pumps

- No water consumption;
- No leaks;
- No excessive corrosion;



Unrivaled performance and flexibility

- Three model to cover complete range
- Long service lifetime



LTH-065



LT-100